

# IXBA-5M-RS

5메가 UHD IR 블릿 IP 카메라



## ▲ 제품특징

- 1/2.8" Sony IMX335 Low Light Cmos 센서
- Max. 5메가 해상도 2592 x 1944 output
- 저조도 0.1Lux
- Day/Night(ICR), AWB, 2D/3D-DNR, IR-CUT
- D-WDR, 모션감지, Privacy Mask, Mirror, Flip
- RTSP, Onvif 17.06 지원
- H.265/H.264 듀얼-스트림 미디어 서버
- P2P 클라우드 서비스
- 멀티 웹브라우저, PC 클라이언트, 모바일 앱 원격 접속
- 낙뢰 보호 4000V
- 방진방수등급 IP66
- Array IR Led 4개,적외선 거리 70-80m
- HD 2.8-12mm VF 렌즈

## ▲ 제품사양

IXBA-5M-RS	
Camera	
Image Sensor	1/2.8" Sony IMX335 CMOS
Effective Pixels	2592(H)×1944 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
Other	AGC, 2/3 DNR, Motion Detection, Privacy Mask, Mirror, Flip
Encode	
Embedded Solution	Mstar MSC316DM
Video Standard	H.265/H.264
Video Resolution	MainStream: 15fps@5MP(2592x1944), 25fps@4MP/3MP, 30fps@1080P/720P Sub stream: D1/VGA(640x480)/360P/QVGA@25fps
Video Bitrates	512Kbps - 6Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
IR Led	
IR Led	4 Array IR Led
IR Distance	70-80 meters
Lens	
Focal length	2.8-12mm VF lens
Optional Function	
POE, Audio	
Network Services	
Protocol	RTSP/FTP/DHCP/DDNS/NTP/SMTP/NFS
P2P	Yes
Web	IE, firefox 32bit ESR
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC ± 10%
Power Consumption	< 5 W
Operating Temp.	-30°C(+60)°C, 10%-90%RH

## ▲ 외관도

