

IXHA-500E

2M FHD IR Housing Camera



▲ Features

- 1/2.8" Sony STARVIS sensor
- FHD resolution 1920 x 1080 output
- Low illumination 0.001Lux
- Day/Night (ICR), AWB, 2D/3D-DNR, IR-CUT
- D-WDR, Motion Detection, Privacy Mask, Mirror, Flip
- RTSP and Onvif 17.06 compatible
- H.265/H.264 dual-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 4pcs Array IR Leds, IR distance 70-80 meters
- HD 2.8-12mm VF lens

▲ Specification

IXHA-500E	
Camera	
Image Sensor	1/2.8" STARVIS
Effective Pixels	1920(H)×1080 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.001Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
Other	AGC, 2/3 DNR, Motion Detection, Privacy Mask, Mirror, Flip
Encode	
Embedded Solution	Mstar MSC316DM
Video Standard	H.265/H.264
Video Resolution	MainStream: 25fps@1080P/720P Sub stream: VGA(640x480)/360P/QVGA@25fps
Video Bitrates	512Kbps - 4Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
IR Led	
IR Led	4 Array IR Led
IR Distance	70-80 meters
Lens	
Focal length	2.8-12mm VF lens
Optional Function	
POE, Audio	
Network Services	
Protocol	RTSP/FTP/DHCP/DDNS/NTP/SMTP/NFS
P2P	Yes
Web	IE, firefox 32bit ESR
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC ± 10%
Power Consumption	< 5 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH