

CXHA-500P

5MP UHD Coaxia Motorized Housing Camera

Coaxia



▲ Features

- H.265/H.264
- 5MP(2592 x 1944)
- 2.8-12mm Motorized Lens
- IR 4pcs, Distance 70-80m
- DWDR/DHDR
- Motion Detection, Privacy Masking, Flip, Mirror
- IP66
- ECP Series Max. 1.2Km BNC 1:N TX Integrated
- NDAA Compliant

▲ Specification

CXHA-500P	
Camera	
Image Sensor	1/2.8" SONY CMOS
Effective Pixels	2592 (H) × 1944 (V)
Electronic Shutter	Auto, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR & HDR
White Balance	Auto
BLC	Support
DNR	2D/3D DNR
Function	Motion Detection, Privacy Masking, Flip, Mirror
Video	
Video Compression	H.265/H.264
Video Resolution	Main stream: 30fps@1080P/720P Sub stream: 30fps@D1/VGA/360P
Video Bitrates	32Kbps - 5Mbps, VBR/CBR
Audio Compression	G.711-u/G.711-a
OSD Overlay	Title and Time Overlay
IR LED	
IR LED	4PCS High-power IR Led
IR Distance	70-80m
Lens	
Lens	2.8-12mm Motorized Lens
Network	
Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
P2P	Support
Web	Edge, Chrome, Firefox
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, POE
Power Supply	12 VDC ± 10%
Power Consumption	< 15W
Operating Temperature & Humidity	-30°C-(+60)°C, 10%-90%RH
IK Rating	-
Ingress Protection	IP66
Dimension	Φ111.7(mm)×457.9(mm)
EOC	
Protocol	IEEE1901 & ETSI TS 105 176
PoC	Power over Coax 57VDC
Bandwidth	95Mbps (Max. 270Mbps)
Applicable RX	ECP-2601R, ECP-2701R, ECP-2808R, ECP-2816R
Transmission Distance	1,200m

▲ Connection Diagram

