

IXBB-500H

8MP UHD Bullet Camera



Specification

IXBB-500H	
Camera	
Image Sensor	1/2.8" SONY CMOS
Effective Pixels	3840 (H) × 2160P (V)
Electronic Shutter	Auto, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR & HDR
White Balance	Auto
BLC	Support
DNR	2D/3D DNR
Function	Motion Detection, Privacy Masking, Flip, Mirror
Video	
Video Compression	H.265/H.264
Video Resolution	MainStream: 20fps@8MP(3840x2160), 30fps@6MP(3072x2048) / 5MP(2592x1944) / 4MP / 3MP / 1080P / 720P,etc. Sub stream: 720x480/ VGA(640x480)/360P/QVGA@30fps,etc.
Video Bitrates	512Kbps - 12Mbps, VBR/CBR
Audio Compression	G.711-u/G.711-a
OSD Overlay	Title and Time Overlay
IR LED	
IR LED	20PCS SMD IR Leds
IR Distance	30-35m
Lens	
Lens	2.7-13.5mm Motorized lens
Network	
Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
P2P	Support
Web	Edge, Chrome, Firefox
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, POE
Power Supply	12 VDC ± 10%
Power Consumption	< 8W
Operating Temperature & Humidity	-30℃-(+60)℃, 10%-90%RH
IK Rating	-
Ingress Protection	IP66
Dimension	Φ82.9(mm)×276.5(mm)

Features

- H.265/H.264
- 8MP(3840 x 2160P)
- 2.7-13.5mm Motorized lens
- IR 20pcs, Distance 30-35m
- DWDR/DHDR
- Motion Detection, Privacy Masking, Flip, Mirror
- IP66
- NDAA Compliant

Dimension

