

IXDA-5M-R

5MP UHD PTZ Dome Camera



Specification

IXDA-5M-R	
Camera	
Image Sensor	1/2.8" SONY CMOS
Effective Pixels	3840 (H) × 2160 (V)
Electronic Shutter	Auto, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR & HDR
White Balance	Auto
BLC	Support
DNR	2D/3D DNR
Function	Motion Detection, Privacy Masking, Flip, Mirror
Video	
Video Compression	H.265/H.264
Video Resolution	Main Stream: 20fps@8MP(3840x2160), 30fps@6MP(3072x2048)/5MP, 4MP/3MP/1080P/720P Sub stream: 25fps@D1/VGA/360P/CIF, etc.
Video Bitrates	512Kbps - 12Mbps, VBR/CBR
Audio Compression	G.711-u/G.711-a
OSD Overlay	Title and Time Overlay
IR LED	
IR LED	3PCS Array IR Leds
IR Distance	20-30M
Lens	
Lens	2.8-8mm motorized lens
IRIS	-
View Angle	-
Zoom	3x optical zoom
Network	
Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
P2P	Support
Web	Edge, Chrome, Firefox
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network	1-RJ45, 100Mbps, POE 48V in
Power Supply	POE(803.af), 12 VDC ± 10%
Power Consumption	< 10 W
Operating Temperature & Humidity	-30°C-(+60)°C, 10%-90%RH
Ingress Protection	IP66
Dimension	Φ105(mm)×73(mm)
Option	
Option	-
PTZ	
Pan/Tilt Range	Pan: 0° ~ 350°; Tilt: 0° ~ 90°
Preset	255
Preset Speed	-
Control Spded	Pan: 0.5° ~80° /s; Tilt: 0.5° ~60° /s
A-B Scanning	-
Auto Cruise	-
Pattern Scanning	-
Power On	-
Power Recovery	Support
Guard Position	-

Features

- H.265/H.264
- 5MP(2592 x 1944)
- 2.8-8mm Motorized, 3x Optical Zoom
- IR 3pcs, Distance 20-30m
- DWDR/DHDR
- Motion Detection, Privacy Masking, Flip, Mirror
- IP66
- NDAA Compliant

Dimension

