

# IXDB-500A 2MP FULL-HD Motorized Dome Camera



## ▲ Features

- H.265/H.264
- 2MP(1920 x 1080)
- 2.7~13.5mm Motorized Lens
- IR 4pcs, Distance 40m
- DWDR/DHDR
- Motion Detection, Privacy Masking, Flip, Mirror
- NDAA Compliant

## ▲ Specification

IXDB-500A	
<b>Camera</b>	
Image Sensor	1/2.8" SONY CMOS
Effective Pixels	1920 (H) x 1080 (V)
Electronic Shutter	Auto, 1/25s ~ 1/100000s
Min. Illumination	0.001Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR & HDR
White Balance	Auto
BLC	Support
DNR	2D/3D DNR
Function	Motion Detection, Privacy Masking, Flip, Mirror
<b>Video</b>	
Video Compression	H.265/H.264
Video Resolution	Main stream:30fps@1080P/720P Sub stream: 30fps@D1/VGA/360P
Video Bitrates	32Kbps - 5Mbps, VBR/CBR
Audio Compression	G.711-u/G.711-a
OSD Overlay	Title and Time Overlay
<b>IR LED</b>	
IR LED	4PCS Array IR Led
IR Distance	40m
<b>Lens</b>	
Lens	2.7-13.5mm Motorized Lens
<b>Network</b>	
Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
P2P	Support
Web	Edge, Chrome, Firefox
Media	CMS, Android, IOS
ONVIF	17.06 compatible
<b>General</b>	
Network Port	1-RJ45, 100Mbps, POE
Power Supply	12 VDC ± 10%
Power Consumption	< 8 W
Operating Temperature & Humidity	-30°C-(+60)°C, 10%-90%RH
IK Rating	-
Ingress Protection	-
Dimension	Φ132(mm)×103.9(mm)

## ▲ Dimension

