

IX-NYU-216


▶ 16-ch 2-SATA Ultra 265/H.265/H.264 NVR



▲ 제품 특징

- Ultra 265/H.265/H.264
- 16ch 입력
- Onvif Profile S, Profile G, Profile T
- 1-ch HDMI, 1-ch VGA
- 최대 4K 해상도 녹화가능
- SATA HDD 2대 최대 6TB
- 클라우드 업그레이드 지원

▲ 외관도



▲ 제품 사양

Model	IX-NYU-216
Video/Audio Input	
IP영상입력	16-ch
양방향 오디오 입력	1-ch, RCA
Network	
수신대역폭	160Mbps
출력대역폭	64Mbps
원격사용자	128
프로토콜	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA 출력	HDMI:4K (3840x2160@30), 1920X1080@60, 1920X1080@50, 1600X1200@60, 1280X1024@60, 1280X720@60, 1024X768@60 VGA:1920X1080@60, 1920X1080@50, 1280X1024@60, 1280X720@60, 1024X768@60
녹화해상도	4K/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
오디오 출력	1-ch, RCA
동시재생	16-ch
복도모드	3/4/5/7/9/10/12/16
CVBS 출력	-
Decoding	
Decoding format	Ultra265/H.265/H.264
Live view/Playback	4K/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30
Hard Disk	
SATA	2 SATA interfaces
Capacity	up to 6TB for each disk
Disk Array Type	-
eSATA	-
miniSAS	-
External Interface	
Network Interface	2 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0 Front panel: 1 x USB2.0
Alarm 입력	-
Alarm 출력	-
Serial Interface	-
USB Interface	-
Decoding Card (Optional)	-
전원출력	-
PoE	
Interface	-
Max Power	-
Supported Standard	-
General	
Power Supply	12V DC Power Consumption: ≤7 W (without HDD)
동작환경	-10°C ~ +55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)
외형치수(W×D×H)	380mm × 315mm × 53mm (15.0" × 12.4" × 2.1")
중량 (without HDD)	≤2.4kg (5.29 lb)
Chassis	-