

FS-1016C

HD-Decoder



Specification

MODEL		FS-1016C
System		Embedded Linux
IP Camera	Input	16 Channels
	Protocol	FOCUS, ONVIF
Display	Speed	120fps
	Screen Mode	16
Video In		IP Camera (Max. 5 Megapixel, Support 2592 x 1944 Resolution) NVR, DVR
Video Out	Monitor Out	HDMI(1), VGA(1)
	Resolution	800x600, 1024x768, 1280x1024, 1920x1080 (선택)
Network		Gigabit Ethernet (RJ45), DHCP & DDNS
Network Fonction		1) Live Monitoring 2) Time Syn NTP ("pool.ntp.org")
Remote management	Web (IE)	System Settings
System Recovery after Power Failure		Auto-Reboot and Journaling File System
Advanced Fonctions		1) FimeWare Update by USB & CMS over Network 2) Import & Export of Setting values 3) Warning Alarm for System Over 4) Digital Zoom
System Operation		USB Mouse/ Remote Control (Option)
Power		12V x 1A D/C
Temperature & Humidity		5~40 °C / 20~90% RH
Dimention (WxDxH)		139 x 123 x 32 (mm)

► Contents of this manual are subject to change without prior notice for reasons such as functionality enhancements.

Features

- Supports up to 16-channel monitoring
- 5 million pixel (2592x1944) resolution decoding support
- ONVIF compatibility & Auto Focus DVR/NVR connection support
- Convenient registration and search function
- System health monitoring function
- Support system, camera bandwidth network status monitoring
- H.264 Support
- Simultaneous HDMI and VGA output

Connection Diagram



Dimension

